

GoFast[®] for ARM and CrossWorks ARM

Features

- Fast
- Reentrant
- ROMable
- Conforms to IEEE 754
- “Link and Go” compiler support for CrossWorks ARM
- Includes complete source, test programs, project files, and startup code

Description

GoFast[®] for ARM was carefully designed for high performance operation in embedded applications and ease of use including “link and go” compatibility with the CrossWorks C compiler. GoFast provides ROMable, reentrant IEEE and ANSI compatible ARM floating point support. It boosts the performance of an application’s math calculations or eliminates the need for a hardware floating-point coprocessor, in order to reduce product manufacturing cost. It is delivered with full assembly source code.

Currently GoFast is offered only for the ARM instruction set, not Thumb or Thumb-2.

Functionality

GoFast ARM offers the following reentrant floating point routines, for both single and double precision:

- **intrinsic basic operations + - * /**
- **intrinsic conversions**
- **sqrt**
- **sin, cos, tan**
- **asin, acos, atan, atan2**
- **sinh, cosh, atanh**
- **log, log10, exp, pow**
- **floor, ceil, fabs**
- **modf, fmod, frexp, ldexp**

Floating Point Technology

GoFast is based on “Architecture Independent Technology” (AIT) and proven floating point algorithms that were developed for over a decade. The algorithms have been thoroughly tested using automated methods.

Conformance and Testing

The accuracy of each GoFast Floating Point Library is within one (least significant) bit for arithmetic functions and two bits for transcendental functions, in most cases. The IEEE 754 Floating Point Format defines special representations for underflow, overflow, and invalid operation. The GoFast routines use these formats and adhere to the IEEE 754 error handling procedures in all applicable cases. Quality assurance and testing procedures have assured proper product operation. In addition, each delivery includes target specific test programs assuring confidence of product operation.

Timings

The following tables give the times for all floating point operations, for GoFast and the CrossWorks floating point library. The times, in microseconds, were measured using the indicated processor and evaluation board. The basic operations (add, subtract, multiply, divide, conversions, and comparisons) in the CrossWorks C library are hand-coded and faster than those in GoFast, so the CrossWorks versions are used instead. (If you only need these basic operations, you don't need GoFast.) Thus, the routines linked are a mixture of both libraries, as indicated in **bold** below. GoFast provides the greatest benefit for the more complex operations, typically offering a 2x to 3x performance boost.

Microsecond Timings

ARM7: AT91SAM7X256-EK, 48 MHz, RAM

Function	Double-Precision		Single-Precision	
	GoFast	CWK	GoFast	CWK
add	2.5	1.6	1.6	1.0
subtract	3.0	2.0	1.9	1.4
multiply	2.7	2.2	1.6	1.0
divide	16.5	9.2	8.3	2.3
sqrt	32.3	46.6	16.7	15.3
exp	13.1	46.6	4.3	32.4
log	27.2	60.2	11.3	28.9
log10	28.3	62.4	11.6	30.0
sin	11.6	41.9	4.0	21.0
cos	10.6	53.1	4.0	25.2
tan	28.2	59.9	11.3	28.5
asin	45.1	109.2	34.8	48.2
acos	43.8	107.6	42.2	46.8
atan	27.1	64.4	11.6	30.2
atan2	42.8	75.5	19.2	34.6
pow	40.5	112.9	16.7	65.8
tanh	30.7	62.5	19.2	40.1
sinh	30.4	65.0	12.1	39.0
cosh	29.8	63.9	11.6	40.6
modf	1.4	1.9	1.1	1.3
fmod	1.6	16.5	1.0	8.0
fabs	0.5	0.5	0.3	0.3
floor	1.1	1.9	0.7	1.2
ceil	1.2	1.9	0.7	1.2
ldexp	2.2	2.3	1.4	1.6
frexp	1.3	1.8	0.8	1.3
cmp	1.7	1.0	1.2	0.8
fp to long	1.0	0.6	0.7	0.5
fp to ulong	1.0	0.5	0.7	0.5
long to fp	4.6	0.8	4.3	0.7
ulong to fp	4.5	0.7	4.2	0.7
sgl to dbl	0.9	0.5	–	–
dbl to sgl	1.1	0.6	–	–